

Cisco Unified IP Phone 7911G

The Cisco® Unified Communications system of voice and IP communications products and applications enables organizations to communicate more effectively—enabling them to streamline business processes, reach the right resource the first time and impact the top and bottom line. The Cisco Unified Communications portfolio is an integral part of the Cisco Business Communications Solution—an integrated solution for organizations of all sizes which also includes network infrastructure, security, and network management products, wireless connectivity, and a lifecycle services approach, along with flexible deployment and outsourced management options, end-user and partner financing packages, and third-party communications applications.

The Cisco Unified IP Phone 7911G fills the communication needs of cubicle, retail, classroom, or manufacturing workers or anyone who conducts low to moderate telephone traffic. Four dynamic soft keys guide users through core business features and functions, while a pixel-based display combines intuitive features, calling information, and extensible Markup Language (XML) services into a rich user experience. The Cisco Unified IP Phone 7911G offers numerous important security features plus the choice of IEEE 802.3af Power over Ethernet (PoE), Cisco inline power, or local power through an optional power adaptor (Figure 1).

Figure 1. Cisco Unified IP Phone 7911G



FEATURES

The Cisco Unified IP Phone 7911G is designed to grow with your organization. A dynamic, soft key-activated feature set enables the phone to keep pace with your requirements through regular software upgrades. Moves, adds, and changes are easy; users can simply pick up their phones and move to a new location anywhere on the network. The Cisco Unified IP Phone 7911G also provides accessibility features to those with special needs. Tables 1–7 present the features, specifications, and compliance information of the Cisco Unified IP Phone 7911G, Table 8 provides ordering information, and Table 9 lists available optional accessories.

Table 1. Features and Their Descriptions

Feature	Description
Lighted Hold Key	Lights when pressed to put a call on hold and stays lit until the held call has been resumed, or flashes if one call is held while another is engaged; is dark when no calls are on hold
Lighted Menu Key	Lights when pressed to access voicemail messages, call logs, network settings, user preferences, corporate directories, and XML services; stays lit while menu items are active
Lighted Message Waiting Indicator	Lights when there is new voicemail and is visible on both the phone chassis and the handset; stays lit until new voicemail has been processed by the user
Graphical Display	Graphical monochrome display with resolution of 192 x 64 pixels provides a scrollable 3-line intuitive access to calling features and text-based XML applications; the Cisco Unified IP Phone 7911G also supports audio-based XML applications
Four Soft-Key Buttons and a Scroll Toggle Bar	Dynamically present calling options to the user; the scroll toggle bar allows easy movement through the displayed information
Network Features	Cisco Discovery Protocol; IEEE 802.1 p/q tagging and switching
Ethernet Switch	10/100BASE-T Ethernet connection through two RJ-45 ports, one for the LAN connection, the other for connecting a downstream Ethernet device such as a PC
Volume Control	A volume-control toggle to provide easy decibel-level adjustments of the handset, monitor speaker, and ringer
Single-Position Foot Stand	Optimum display viewing and comfortable use of buttons and keys; the foot stand can be removed for wall mounting with mounting holes located on the base of the phone
Multiple Ring Tones	More than 24 user-adjustable ring tones
American Disabilities Act (ADA) Features	Hearing-aid-compatible (HAC) handset that meets the requirements set by the ADA; it also meets ADA HAC requirements for a magnetic coupling to approved hearing aids. The phone dialing pad also complies with the ADA □
Signaling Protocol Support	Compatible with Cisco CallManager Version 3.3(5) and later, using the Skinny Client Control Protocol (SCCP)
Codec Support	G.711a, G.711, G.729a, G.729b, and G.729ab audio-compression codecs
Configuration Options	Provisioning of network parameters through Dynamic Host Configuration Protocol (DHCP)
Voice Quality	Comfort-noise generation and voice-activity-detection (VAD) programming on a system basis

Table 2. Security Features

Item	Description
Certificates	Phones are shipped with factory-installed X.509v3 certificates. There is also an option of installing and removing certificates at the customer's site.
Device Authentication and Signaling Encryption	Transport layer security (TLS) with AES-128 encryption is offered when using Cisco Unified CallManager Version 4.1 or later.
Media Encryption	Secure Real-Time Transport Protocol (SRTP) with AES-128 encryption is offered when using Cisco Unified CallManager Version 4.1 or later.

Table 3. Software and Physical Specifications

Item	Description
Firmware Upgrades	Download firmware changes from Cisco Unified CallManager and Cisco.com
Software Upgrades	Software upgrade supported using a Trivial File Transfer Protocol (TFTP) server
Dimensions (H x W x D)	6.5 x 7 x 6 in. (20.3 x 17.67 x 15.2 cm)
Weight	1.9 lb (0.9 kg)
Phone Casing Composition	Polycarbonate acrylonitrile butadiene styrene (ABS) plastic in textured dark gray with silver-colored bezel

Table 4. Power Options

Item	Description
Cisco PoE	Works with Cisco PoE from any Cisco Inline Power-capable switch
IEEE 802.3af PoE	Can receive power from IEEE 802.3af-compliant blades
Local Power	Can also be powered locally with a power adapter (CP-PWR-CUBE-3=) along with one of the power cords listed in Table 5

Table 5. AC Region and County-Specific Power Cords

Part Number	Description
CP-PWR-CORD-AP=	Asia Pacific
CP-PWR-CORD-AR=	Argentina
CP-PWR-CORD-AU=	Australia
CP-PWR-CORD-CE=	European Community
CP-PWR-CORD-CN=	China
CP-PWR-CORD-JP=	Japan
CP-PWR-CORD-NA=	North America
CP-PWR-CORD-SW=	Switzerland
CP-PWR-CORD-UK=	United Kingdom

Table 6. Temperature Ratings

Item	Description
Operating Temperature	32 to 104°F (0 to 40°C)
Relative Humidity	10 to 95% (noncondensing)
Storage Temperature	14 to 140°F (-10 to 60°C)

Table 7. Certifications

Item	Description
Regulatory Compliance	CE Marking
Safety	<ul style="list-style-type: none">• Underwriters Laboratories (UL) 60950• Canadian Standards Association (CSA) C22.2 No. 60950• EN 60950• IEC 60950• AS/NZS60950• TS 001
Electromagnetic Compatibility	<ul style="list-style-type: none">• Federal Communications Commission (FCC) Part 15 (CFR 47) Class B• ICES-003 Class B• EN55022 Class B• CISPR22 Class B• AS/NZS CISPR 22 Class B• CISPR 24• VCCI Class B• EN55024• EN 50082-1• EN 61000-3-2• EN 61000-3-3• EN 61000-6-1
Telecom	<ul style="list-style-type: none">• FCC Part 68 (CFR47) HAC• TIA 810A

Table 8. Ordering Information

Part Number	Description
CP-7911G	Cisco Unified IP Phone 7911G
CP-7911G=	Cisco Unified IP Phone 7911G, Spare
CP-7911G-CH1	Cisco Unified IP Phone 7911G, for Channels, with one station user license

Note: All Cisco Unified IP phones require the purchase of a phone technology license, regardless of call protocol being used.

Table 9. Optional Accessories

SKU	Description
CP-HANDBSET=	Spare phone handset
CP-HANDBSET-CORD=	Spare phone handset cord
CP-LCKNGWALLMOUNT2=	Universal locking wall-mounting kit
CP-PWR-CUBE-3=	Local power adapter for sites where PoE is not available; refer to Table 5 for the right power cord part number for your region

WARRANTY

Cisco Unified IP phones are covered by a Cisco standard 1-year hardware warranty.

CISCO UNIFIED COMMUNICATIONS SERVICES AND SUPPORT

Using the Cisco Lifecycle Services approach, Cisco Systems® and its partners offer a broad portfolio of end-to-end services to support the Cisco Unified Communications system. These services are based on proven methodologies for deploying, operating, and optimizing IP communications solutions. Upfront planning and design services, for example, can help you meet aggressive deployment schedules and minimize network disruption during implementation. Operate services reduce the risk of communications downtime with expert technical support. Optimize services enhance solution performance for operational excellence. Cisco and its partners offer a system-level service and support approach that can help you create and maintain a resilient, converged network that meets your business needs.

**Corporate Headquarters**

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel
Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan
Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)

